

カムロック 633-FB 選定ガイド

■ カムロック 633シリーズ アダプター オネジ 規格

材質		品番	呼び径		寸法 (mm)							単位		価格
			インチ	ミリ	D	E	F	H	L	M	個	円/個		
アルミ合金製	RoHS2 本体材質 / ADC12 (一部を除く)	633-FB 1/2AL	1/2"	15	14			35	32	59	16	54		
		633-FB 3/4AL	3/4"	20	20			35	32	59	16	54		
		633-FB 1AL	1"	25	24			41	37	73	18	42		
		633-FB 1-1/4AL	1-1/4"	32	29			48	45	82	21	30		
		633-FB 1-1/2AL	1-1/2"	40	37			59	53	85	21	20		
		633-FB 2AL	2"	50	48			68	63	95	25	20		
		633-FB 2-1/2AL	2-1/2"	65	56			84	76	102	29	12		
		633-FB 3AL	3"	80	73			100	92	106	31	9		
		633-FB 4AL	4"	100	98			129	120	123	37	4		
		633-FB 5AL	5"	125	121			149	146	125	38	4		
		633-FB 6AL	6"	150	149			196	176	127	37	2		
ステンレススチール製	RoHS2 本体材質 / SCS14 (SUS316 相当)	633-FB 1/2SST	1/2"	15	14			35	32	59	16	54		
		633-FB 3/4SST	3/4"	20	20			35	32	59	16	54		
		633-FB 1SST	1"	25	24			41	37	73	18	42		
		633-FB 1-1/4SST	1-1/4"	32	29			48	45	82	21	30		
		633-FB 1-1/2SST	1-1/2"	40	37			59	53	85	21	20		
		633-FB 2SST	2"	50	48			68	63	95	25	20		
		633-FB 2-1/2SST	2-1/2"	65	56			84	76	102	29	12		
		633-FB 3SST	3"	80	73			100	92	106	31	9		
		633-FB 4SST	4"	100	98			129	120	123	37	4		
		633-FB 5SST	5"	125	121			149	146	122	38	4		
		633-FB 6SST	6"	150	149			196	176	127	38	2		
ポリプロピレン製 (ガラス繊維入り)	RoHS2 本体材質 / PP	633-FB 3/4PP	3/4"	20	20	19		42	32	74	20	54		
		633-FB 1PP	1"	25	22	24		51	37	84	20	42		
		633-FB 1-1/2PP	1-1/2"	40	38	38		67	54	92	22	20		
		633-FB 2PP	2"	50	48	48		81	63	104	24	12		
		633-FB 3PP	3"	80	74	72		108	92	130	31	9		
ブロンズ製	本体材質 / CAC406 (BC6) 青銅	633-FB 1/2BR	1/2"	15	14			35	32	59	18	54		
		633-FB 3/4BR	3/4"	20	20			35	32	59	17	54		
		633-FB 1BR	1"	25	24			41	37	72	20	42		
		633-FB 1-1/4BR	1-1/4"	32	29			48	45	80	22	30		
		633-FB 1-1/2BR	1-1/2"	40	37			58	53	79	19	20		
		633-FB 2BR	2"	50	46			67	63	90	25	20		
		633-FB 2-1/2BR	2-1/2"	65	56			84	76	102	27	12		
		633-FB 3BR	3"	80	73			99	92	103	28	9		
		633-FB 4BR	4"	100	96			129	120	119	32	4		

※ RoHS2指令適合品

△ 「安全にご使用いただくための注意事項」を必ずご確認ください。