

piNLINE® vacuum generator MINI Xi, 6-6 mm, 0122895



- Patented COAX® cartridge technology.
- High vacuum flow capacity in relation to energy consumption.
- Low weight inline design with push-in fittings for vacuum and compressed air.
- Quick and easy installation directly on the hose.
- Si cartridge for extra vacuum flow.
- Pi cartridge for high performance at low feed pressures.
- Xi cartridge when high flow and deep vacuum is needed.

一般情報

材質	CuZn, PA, SS, Al, ニトリルゴム (NBR)
ノイズ レベル	81 – 85 dBA
温度	-10 – 80 °C
重量	23 g

性能

最大供給圧力	0.7 MPa
--------	---------


Vacuum flow

Feed pressure	Air consumption	Vacuum flow (NI/s) at different vacuum levels (-kPa)											Max vacuum
MPa	NI/s	0	10	20	30	40	50	60	70	80	90	-kPa	
0.5	0.46	0.62	0.5	0.37	0.27	0.19	0.15	0.11	0.07	0.045	0.011	94	

排気時間 (s/l)

Feed pressure	Air consumption	排気時間 (s/l) to reach different vacuum levels (-kPa)											Max vacuum
MPa	NI/s	10	20	30	40	50	60	70	80	90	-kPa		
0.5	0.46	0.18	0.41	0.72	1	1.6	2.3	3.5	5.3	8.9	94		

Dimensional drawings



データシートに記されている値は、以下の環境でテストして得られた値です：

室温	(20° C [68° F] ± 3° C [5.5° F])
標準大気圧	(101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg])
相対湿度	0-100%
圧縮空気の品質	DIN ISO 8573-1 class 4

Accessories

	Item no.
Snap-in piINLINE® 4x MINI mounting bracket	0123094
Silencer piINLINE® MINI	0125466
Snap-in piINLINE® 1x MINI mounting bracket for silencer	0126009