

種類豊富な接続。
様々なアプリケーションにご利用頂けます。

仕様

材質: 真鍮 (鍍金処理)
最高使用圧力: 3.5 MPa (507 PSI)

	品番	接続1	接続2		品番	接続1	接続2
ホースニップル (オネジ×ホース) 	19-900-0211	R 1/8"	5 mm (3/16")	六角ニップル (オネジ×オネジ) 	19-900-1210	G 1/8"	G 1/8"
	19-900-0212	R 1/8"	6.3 mm (1/4")		19-900-1212	G 1/4"	G 1/4"
	19-900-0221	R 1/4"	5 mm (3/16")		19-900-1221	R 3/8"	R 3/8"
	19-900-0222	R 1/4"	6.3 mm (1/4")		19-900-1224	G 3/8"	G 3/8"
	19-900-0223	R 1/4"	8 mm (5/16")		19-900-1235	G 1/2"	G 1/2"
	19-900-0224	R 1/4"	10 mm (3/8")		19-900-1236	R 1/2"	R 1/2"
	19-900-0225	R 1/4"	13 mm (1/2")		19-900-1246	R 3/4"	R 3/4"
	19-900-0232	R 3/8"	6.3 mm (1/4")		19-900-1249	G 3/4"	G 3/4"
	19-900-0233	R 3/8"	8 mm (5/16")		19-900-1268	R 1"	R 1"
	19-900-0234	R 3/8"	10 mm (3/8")		19-900-1269	G 1"	G 1"
	19-900-0235	R 3/8"	13 mm (1/2")	異径六角ニップル (オネジ×オネジ) 	19-900-1211	G 1/4"	G 1/8"
	19-900-0242	R 1/2"	6.3 mm (1/4")		19-900-1214	G 1/4"	G 3/8"
	19-900-0243	R 1/2"	8 mm (5/16")		19-900-1215	G 1/4"	G 1/2"
	19-900-0244	R 1/2"	10 mm (3/8")		19-900-1220	G 3/8"	G 1/8"
	19-900-0245	R 1/2"	13 mm (1/2")		19-900-1222	R 3/8"	R 1/2"
	19-900-0246	R 1/2"	16 mm (5/8")		19-900-1225	G 3/8"	G 1/2"
	19-900-0247	R 1/2"	19 mm (3/4")		19-900-1227	G 3/8"	G 3/4"
	19-900-0254	R 3/4"	10 mm (3/8")		19-900-1229	G 1/2"	G 3/4"
	19-900-0255	R 3/4"	13 mm (1/2")		19-900-1237	R 1/2"	R 3/4"
	19-900-0256	R 3/4"	16 mm (5/8")		19-900-1247	R 3/4"	R 1"
ホース継手 (ホース×ホース) 	19-900-0257	R 3/4"	19 mm (3/4")	Y型コネクター (メネジ×メネジ×メネジ) 	19-900-1248	G 3/4"	G 1"
	19-900-0258	R 3/4"	25 mm (1")		19-900-5902	G 1/2"	G 1/2"
	19-900-0267	R 1"	19 mm (3/4")		19-900-5912	G 3/8"	G 3/8"
	19-900-0268	R 1"	25 mm (1")	Y型コネクター (オネジ×メネジ×メネジ) 	19-900-5916	G 1/4"	G 1/4"
	19-900-0262	6.3 mm (1/4")	6.3 mm (1/4")		19-900-5920	G 1/4" (メネジ)	R 1/4" (オネジ)
	19-900-0264	10 mm (3/8")	10 mm (3/8")		19-900-5921	G 3/8" (メネジ)	R 3/8" (オネジ)
	19-900-0265	13 mm (1/2")	13 mm (1/2")		19-900-5925	G 1/2" (メネジ)	R 1/2" (オネジ)