


パイプ PIPE

パイプ Pipe



HI-PVC

呼び径 A	Size B	D	t	重量 Weight (kg/m)
13	3/8	18.0	2.5	0.170
16	1/2	22.0	3.0	0.251
20	3/4	26.0	3.0	0.303
25	1	32.0	3.5	0.439
30	1-1/4	38.0	3.5	0.531
40	1-1/2	48.0	4.0	0.774
50	2	60.0	4.5	1.098
65	2-1/2	76.0	4.5	1.415
75	3	89.0	5.9	2.156
100	4	114.0	7.1	3.338
125	5	140.0	7.5	4.370
150	6	165.0	9.6	6.561
200	8	216.0	11.0	9.918
250	10	267.0	13.6	15.157
300	12	318.0	16.2	21.504

単位Unit: mm

HT(C-PVC)

呼び径 A	Size B	D	t	重量 Weight (kg/m)
16	1/2	22.0	3.0	0.265
20	3/4	26.0	3.0	0.321
25	1	32.0	3.5	0.464
30	1-1/4	38.0	3.5	0.561
40	1-1/2	48.0	4.0	0.818
50	2	60.0	4.5	1.161
65	2-1/2	76.0	5.0	1.628
75	3	89.0	5.8	2.213
100	4	114.0	7.0	3.435
125	5	140.0	8.2	4.957
150	6	165.0	9.7	6.910


単位Unit: mm

寸法は JIS K 6776 に準拠
Dimensions are in accordance with JIS K 6776

寸法は JIS K 6741 に準拠
Dimensions are in accordance with JIS K 6741

継手 FITTINGS

継手受口共通寸法 Socket Dimension



- 65A以上は「J」の形状になります。
The shape of the socket end in 65A and above is «J» as illustrated.

HI-PVC

呼び径 A	Size B	D	t	d ₁	L	d
13	3/8	24	3.0	18.40	26	13
16	1/2	29	3.5	22.40	30	16
20	3/4	33	3.5	26.45	35	20
25	1	40	4.0	32.55	40	25
30	1-1/4	46	4.0	38.60	44	31
40	1-1/2	57	4.5	48.70	55	40
50	2	70	5.0	60.80	63	51
65	2-1/2	87	6.6	76.60	61	67
75	3	102	8.0	89.60	64	77
100	4	130	10.0	114.70	84	100
125	5	157	11.0	140.85	104	125
150	6	186	13.0	166.00	132	146
※200	8	243	13.0	217.4	145	196
※250	10	300	14.5	268.6	175	242
※300	12	356	16.0	319.8	185	288

単位Unit: mm

HT(C-PVC)

呼び径 A	Size B	D	t	d ₁	L	d
16	1/2	29	3.5	22.35	27	17
20	3/4	34	4.0	26.35	33	21
25	1	41	4.0	32.50	38	26
30	1-1/4	46	4.5	38.50	42	34
40	1-1/2	56	4.5	48.50	47	40
50	2	69	5.0	60.50	52	50
65	2-1/2	91	6.1	76.70	70	68
75	3	106	7.0	89.70	75	78
100	4	134	9.4	114.85	94	102
125	5	166	10.4	140.80	104	125
150	6	189	12.2	166.00	132	146

単位Unit: mm

注1: 受口寸法及び全長は JIS K 6777 に準拠
Note1: Dimensions are in accordance with JIS K 6777

注1: 受口寸法及び全長は JIS K 6743 に準拠
Note1: Dimensions are in accordance with JIS K 6743
※200~300A の D, t, d₁, L は品種により多少異なりますので、承認図で確認をお願いします。
Since there are some differences among types of fittings in their D, t, d₁ and L for 200~300A, confirm them in the approval drawing.


■最高許容圧力 (MPa)

呼び径 Size	HI-PVC	HT
15-150A	1.0	1.0
200-250A	0.75 (1.0)	
300A	0.6 (1.0)	


※1: () 内は FRP 補強品の数値です。
Note1: () is a pressure for Fiber Reinforced fitting.
※2: プッシュタイプ、ユニフィットの200~300Aの耐圧は0.6MPaです。
Note2: Max. Working Pressure for 200~300A for Bush type, Unifit is 0.6MPa.
※3: 止水フランジは、P.13 をご覧ください。
Note3: Please refer to P.13 about the pressure of Blind Flange.

ソケット COUPLING


同径ソケット Coupling



13~50



65~150




破線はFRP補強品の1.0MPa仕様です。
Dashed shape for Fiber Reinforced: 1.0MPa fitting.


HI-PVC

呼び径 Size	D	L	Z	重量 Weight (kg)
13	24	57	5	0.018
16	29	67	7	0.028
20	33	77	7	0.040
25	40	87	7	0.061
30	46	95	7	0.078
40	57	117	7	0.142
50	70	133	7	0.210
65	87	145	23	0.366
75	102	155	27	0.515
100	130	200	32	1.077
125	157	240	32	1.715
150	186	300	36	2.846
200	243	300	10	3.450
250	300	384	34	6.660
300	356	408	38	8.860

単位Unit: mm



15~50



65~150

HT(C-PVC)

呼び径 Size	D	L	Z	重量 Weight (kg)
16	31	56	5	0.033
20	36	76	5	0.058
25	42	86	5	0.077
30	48	86	6	0.083
40	58	97	6	0.142
50	70	107	6	0.195
65	87	145	6	0.298
75	102	155	9	0.493
100	130	201	12	1.102
125	157	239.5	28.5	1.840
150	186	295.5	28.5	3.068

単位Unit: mm