

ADHESION OIL SPRAY (OSN-420)	SDS No.	582837
TRUSCO NAKAYAMA CORPORATION	Revision Date	May. 26, 2025

SAFETY DATA SHEET(SDS)

1 PRODUCT AND COMPANY IDENTIFICATION

Product Name : ADHESION OIL SPRAY (OSN-420)
 Company Name : TRUSCO NAKAYAMA CORPORATION
 Address : 28-1 SHINBASHI 4-chome, MINATO-KU, TOKYO, JAPAN
 Phone Number : 0120-509-849
 Fax Number : 0120-509-839
 Mail Address : techno.center@trusco.co.jp

2 HAZARDS IDENTIFICATION

Hazards Category
 Aerosols : Category 1
 Flammable Liquids : Category 2
 Skin Corrosion/Irritation : Category 2
 Serious Eye Damage/Eye Irritation : Category 2A
 Specific Target Organ Systemic Toxicity(Single Exposure) : Category 2
 Specific Target Organ Systemic Toxicity(Single Exposure) : Category 3
 Specific target organ systemic toxicity(Repeated exposure) : Category 1
 Aspiration Hazard : Category 1
 Hazardous to The Aquatic Environment(Acute) : Category 1
 Hazardous to The Aquatic Environment(Chronic) : Category 2

The one without the description cannot be classified.

Allocation of Label Elements

Pictogram

Flame
 Exclamation mark
 Health Hazard
 Environment



Signal Word

Danger

Hazard Statement

Extremely flammable aerosol
 Pressurized container : may burst if heated
 Highly flammable liquid and vapour
 Cause skin irritation
 Cause serious eye irritation
 May cause damage to organs
 May cause respiratory irritation; or May cause drowsiness or dizziness
 Causes damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 Very toxic to aquatic life
 Toxic to aquatic life with long lasting effects

Precautionary Statement

Prevention

Before use, read the safe data sheet (SDS).
 Keep out of reach of children.
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 Do not spray on an open flame or other ignition source.
 Use explosion-proof electrical/ventilating/lighting/equipment.

ADHESION OIL SPRAY (OSN-420)	SDS No.	582837
TRUSCO NAKAYAMA CORPORATION	Revision Date	May. 26, 2025

Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Do not burn, even after use.
 Do not breathe dust/fume/gas/mist/vapours/spray.
 Wash points of contact thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Avoid release to the environment.
 Wear protective gloves/protective clothing/eye protection/face protection/respiratory protection.

Response

In case of fire : Use dry chemical, carbon dioxide(CO₂), and foam to extinguish.
 IF SWALLOWED : Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.
 IF ON SKIN : Wash with plenty of soap and water.
 If skin irritation or rash occurs : Get medical advice/attention.
 IF INHALED : Remove person to fresh air and keep comfortable for breathing.
 Get medical advice/attention if you feel unwell.
 IF IN EYES : Rinse cautiously with water for several minutes. Get medical advice/attention.
 If exposed or concerned : Get medical advice/attention.
 Take off contaminated clothing.
 Wash contaminated clothing before reuse.
 Absorb spillage to prevent material damage.
 Collect spillage.

Storage

Store locked up.
 Store in a well-ventilated place. Keep container tightly closed. Keep cool.
 Protect from sunlight. Do not expose to temperatures exceeding 40°C.

Disposal

Dispose of contents /container in accordance with local/regional/national/international regulations.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients and Contents

Component name	CAS number	wt%
Mineral oil	Trade secret	25~35
Organomolybdenum compound	Trade secret	<1
Nonane	111-84-2	10~20
Octane	111-65-9	20~30
Propane	74-98-6	10~20
Butane	106-97-8	5~15

4 FIRST-AID MEASURES

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 Call a physician if you feel unwell.

Skin

Wash with plenty of soap and water.
 Call a physician if you feel unwell.

Eye

Immediately flush eyes with plenty of water for at least 15 minutes.
 Call a physician.

Ingestion

Rinse mouth. Do not induce vomiting.
 Call a physician.

5 FIRE-FIGHTING MEASURES

Extinguishing Media

Dry chemical, carbon dioxide(CO₂), and foam

Specific Fire Fighting

ADHESION OIL SPRAY (OSN-420)	SDS No.	582837
TRUSCO NAKAYAMA CORPORATION	Revision Date	May. 26, 2025

Must not use water to extinguish fires.

Quickly removed from the surrounding flammable.

The use of extinguishing agents specified.

Fire fighting is done from the windward.

On small fires use carbon dioxide (CO₂) or dry chemical.

On large fires use dry chemical or foam.

Sealed containers that are exposed to high temperatures over the water to cool.

Protection for Fire-fighter

Wear full body protective clothing with breathing apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions

Wear protective equipments in case of operation.

Environmental Precautions

Avoid release to the environment.

Methods for Cleaning Up

Remove potential ignition source in vicinity as soon as possible.

Prepare extinguishing agent.

Prevent leakage by enclosing with nonflammables and collect into empty container by scoop or the like.

Absorbed to non-flammable dry sand, if a large amount of spill to prevent enclosed in embankment.

If do not stop the leakage from the container, releasing carried away in a place not at risk of being open.

Spilled material is collected in a container that can be sealed, then remove to safe place.

Deposits, waste treatment is based on the local regulations.

Working from the windward, to evacuate people downwind.

7 HANDLING AND STORAGE

Handling

Use in a well ventilated area.

Keep away from heat, spark and flames.

Use spark-proof tools and explosion-proof equipment.

After handling, wash well hands and face and rinse your mouth.

Facilities storing or utilizing this material should be equipped with an eye wash facility and a safety shower.

Leakage, overflow, to prevent scattering, we do not generate steam in vain.

In the handling area and deny unnecessary entry.

Resting place shall not bring contaminated protective equipment such as gloves.

Wear protective equipments when risk of exposure occurs.

To work in an enclosed area that you work with appropriate protective equipment with a local exhaust ventilation sufficient.

Precautions

Do not breathe vapor or mist.

Handling of the outdoors, as much as possible to work from the windward.

Note is flammable at higher temperatures.

Do not handle in a fire place.

Do not handle in the place more than 40 °C.

Do not use continuously for more than 30 seconds.

Do not store near heat or open flame areas exposed to direct sunlight.

Not want to use toward food and the human body.

Handling Precautions for Safety

Avoid physical damage to containers.

Storage

Fire prohibited strictly.

Do not store in direct sunlight or where more than 40 °C.

Keep away from sources of ignition.

Store in a cool, dry, well-ventilated area away from incompatible substances.

Note that because there is a risk of corrosion and rupture the container is stored in a moisture or humid place.

Store in a tightly closed container.

Safe containers and packaging materials

None in particular.

ADHESION OIL SPRAY (OSN-420)	SDS No.	582837
TRUSCO NAKAYAMA CORPORATION	Revision Date	May. 26, 2025

8 EXPOSURE/PERSONAL PROTECTION

Engineering Controls

- Handling equipment is used explosion-proof.
- Attach an exhaust device to prevent vapor from staying.
- That the equipment and shall become hot, and the source of ignition in the vicinity of the location, such as handling not been placed.
- Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Exposure Limit Values

Chemical name	ACGIH
Mineral oil	TWA 5mg/m ³ (mist)
Nonane	TWA 200ppm
Octane	TWA 300ppm
Propane	TWA 1,000ppm
Butane	TWA -, STEL (1000ppm)

Personal Protective Equipment

Respiratory Protection

- Wear an organic gas mask or positive pressure air respirator if necessary.

Skin Protection

- Solvent-resistant gloves

Eye Protection

- Wear chemical worker's goggles.

Skin and body protection

- Such as long-sleeved work clothes

Hygiene measures

- Do not eat, drink or smoke during work.
- Replacement of the adsorbent, such as the mask is performed each time or use plans.

9 PHYSICAL AND CHEMICAL PROPERTIES

Physical State	:	Liquid	(Base liquid)
Color	:	Yellow	
Odor	:	Solvent odor	
pH	:	Not available	
Boiling Point(°C)	:	Not available	
Melting Point(°C)	:	Not available	
Flammability	:	Not available	
Flash point(°C)	:	10	
Auto-ignition Temperature(°C)	:	Not available	
Flammability or Explosive Limits			
Lower	:	Not available	
Upper	:	Not available	
Vapour Pressure (KPa)	:	Not available	
Vapour Density	:	Not available	
Relative density(g/cm ³)	:	0.80	
Solubility	:	Insoluble in water	
Partition Coefficient: n-octanol/water	:	Not available	
Decomposition Temperature(°C)	:	Not available	
Dynamic viscosity rate	:	Not available	
Relative gas density	:	Not available	
Particle properties	:	Not available	

10 STABILITY AND REACTIVITY

Stability

- Stable under normal temperatures and pressures.

ADHESION OIL SPRAY (OSN-420)	SDS No.	582837
TRUSCO NAKAYAMA CORPORATION	Revision Date	May. 26, 2025

Reactivity

No self-reactive

Conditions to Avoid

Heat, flames, ignition sources and incompatibles.

Hazardous Decomposition Products

Carbon monoxide, carbon dioxide and other oxidized substances.

11 TOXICOLOGICAL INFORMATION

Chemical name	Acute toxicity (oral)	Acute toxicity (dermal)	Acute toxicity (inhalation: gas)	Acute toxicity (inhalation: vapour)	Acute toxicity (inhalation: dust, mist)	Skin corrosion / irritation	Serious eye damage / eye irritation
Mineral oil	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible
Organomolybdenum compound	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible
Nonane	Classification not possible	Classification not possible	Not applicable to category	Category 4	Not applicable to category	Category 2	Category 2B
Octane	Classification not possible	Classification not possible	Not applicable to category	Classification not possible	Not applicable to category	Category 2	Category 2A
Propane	Not applicable to category	Not applicable to category	Not applicable to category	Not applicable to category	Not applicable to category	Not applicable to category	Classification not possible
Butane	Not applicable to category	Not applicable to category	Not applicable to category	Not applicable to category	Not applicable to category	Classification not possible	Classification not possible

Chemical name	Respiratory/skin sensitizer	Germ cell mutagenicity	Carcinogenicity	Toxic to reproduction	Specific target organs/systemic toxicity following single exposure	Specific target organs/systemic toxicity following repeated exposure	Aspiration hazard
Mineral oil	Respiratory sensitizer: Classification not possible; Skin sensitizer: Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible
Organomolybdenum compound	Respiratory sensitizer: Classification not possible; Skin sensitizer: Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible
Nonane	Respiratory sensitizer: Classification not possible; Skin sensitizer: Classification not possible	Classification not possible	Classification not possible	Classification not possible	Category 2 (central nervous system); Category 3 (respiratory tract irritation, narcotic effects)	Classification not possible	Category 1

ADHESION OIL SPRAY (OSN-420)	SDS No.	582837
TRUSCO NAKAYAMA CORPORATION	Revision Date	May. 26, 2025

Octane	Respiratory sensitizer: Classification not possible; Skin sensitizer: Classification not possible	Classification not possible	Classification not possible	Classification not possible	Category 3 (respiratory tract irritation, narcotic effects)	Classification not possible	Category 1
Propane	Respiratory sensitizer: Classification not possible; Skin sensitizer: Classification not possible	Classification not possible	Classification not possible	Classification not possible	Category 3 (narcotic effects)	Classification not possible	Not applicable to category
Butane	Respiratory sensitizer: Classification not possible; Skin sensitizer: Classification not possible	Classification not possible	Classification not possible	Classification not possible	Category 3 (narcotic effects)	Category 1 (central nervous system)	Not applicable to category

12 ECOLOGICAL INFORMATION

Chemical name	Hazardous to the aquatic environment (Acute)	Hazardous to the aquatic environment (Chronic)	Hazard to the ozone layer	Residuality and decomposition	Ecological accumulation	Mobility in soil
Mineral oil	Classification not possible	Classification not possible	Classification not possible	No data	No data	No data
Organomolybdenum compound	Classification not possible	Classification not possible	Classification not possible	No data	No data	No data
Nonane	Category 1	Category 1	Classification not possible	No data	No data	No data
Octane	Category 1	Category 2	Classification not possible	No data	No data	No data
Propane	Classification not possible	Classification not possible	Classification not possible	No data	No data	No data
Butane	Classification not possible	Classification not possible	Classification not possible	No data	No data	No data

13 DISPOSAL CONSIDERATIONS

Dispose of contents /container in accordance with local/regional/national/international regulations.

14 TRANSPORT INFORMATION

UN Class

Aerosols, flammable, Class 2.1

UN No.

UN1950

Packing Group

Not regulated.

15 REGULATORY INFORMATION

ADHESION OIL SPRAY (OSN-420)	SDS No.	582837
TRUSCO NAKAYAMA CORPORATION	Revision Date	May. 26, 2025

Follow all regulations in your country.

16 OTHER INFORMATION

References

JIS Z 7253 (2019)

GHS data-base (NITE)

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if the company has been advised of the possibility of such damages.