



材質：ステンレス（SUS304）

表面処理：なし

品番	呼び	長さ	B	k	b	a	品番	呼び	長さ	B	k	b	a
B64-1215	1.2	15	1	2	3	2.5	B64-2540	2.5	40	2.3	4.6	5	2.5
B64-1220	1.2	20	1	2	3	2.5	B64-2545	2.5	45	2.3	4.6	5	2.5
B64-1225	1.2	25	1	2	3	2.5	B64-2550	2.5	50	2.3	4.6	5	2.5
B64-1615	1.6	15	1.4	2.8	3.2	2.5	B64-0330	3.0	30	2.7	5.5	6	3.2
B64-1620	1.6	20	1.4	2.8	3.2	2.5	B64-0335	3.0	35	2.7	5.5	6	3.2
B64-1625	1.6	25	1.4	2.8	3.2	2.5	B64-0340	3.0	40	2.7	5.5	6	3.2
B64-1630	1.6	30	1.4	2.8	3.2	2.5	B64-0345	3.0	45	2.7	5.5	6	3.2
B64-1635	1.6	35	1.4	2.8	3.2	2.5	B64-0350	3.0	50	2.7	5.5	6	3.2
B64-1640	1.6	40	1.4	2.8	3.2	2.5	B64-0360	3.0	60	2.7	5.5	6	3.2
B64-0215	2.0	15	1.8	3.6	4	2.5	B64-0440	4.0	40	3.7	7.4	8	4
B64-0220	2.0	20	1.8	3.6	4	2.5	B64-0445	4.0	45	3.7	7.4	8	4
B64-0225	2.0	25	1.8	3.6	4	2.5	B64-0450	4.0	50	3.7	7.4	8	4
B64-0230	2.0	30	1.8	3.6	4	2.5	B64-0460	4.0	60	3.7	7.4	8	4
B64-0235	2.0	35	1.8	3.6	4	2.5	B64-0470	4.0	70	3.7	7.4	8	4
B64-0240	2.0	40	1.8	3.6	4	2.5	B64-0540	5.0	40	4.6	9.2	10	4
B64-0245	2.0	45	1.8	3.6	4	2.5	B64-0545	5.0	45	4.6	9.2	10	4
B64-0250	2.0	50	1.8	3.6	4	2.5	B64-0550	5.0	50	4.6	9.2	10	4
B64-2520	2.5	20	2.3	4.6	5	2.5	B64-0560	5.0	60	4.6	9.2	10	4
B64-2525	2.5	25	2.3	4.6	5	2.5	B64-0570	5.0	70	4.6	9.2	10	4
B64-2530	2.5	30	2.3	4.6	5	2.5	B64-0580	5.0	80	4.6	9.2	10	4
B64-2535	2.5	35	2.3	4.6	5	2.5							

作成日

2008. 1. 15

検図

中田

TRUSCO トラスコ中山株式会社

品名

割ピン

品番

B 6 4 - 〇 〇 〇 〇