		2								1					
	THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USE										'AY DETRIME	NTAL TO THE	INTERESTS (DF PANDUIT CORP.	
				\A/I	RE RANGE	IGE			DIMENSIONS in. [mm]	WIRE STRIP LENGTH			
	PANDUIT PART #			WIRE R AW [mm		TAB SIZE in. [mm]	HOUSING COLOR	MAX WIRE INSUL DIA	L ± .04 [1,1]	W ± .01 [0,3]	M ± .02	in. [mm] +1/32 [0,8] -0	TOOLS		
		EDV18-1	187MB		#22-16 [0.5-1.5]		RED	0.145 [3.7]	0.75 [19.0]	0.19 [4.8]	.39 [10.0]	9/32	KST2000C		
		EDV14-	187MB		#16-14 [1.5-2.5]		BLUE	0.165 [4.2]	0.75 [19.0]	0.19 [4.8]	.39 [10.0]	[6.8]	K312000C		
B				·										SERRATED BARREL	B
	NOTES: 1. UL LISTED FOR: A. STRANDED COPPER WIRE ONLY - INTERNAL WIRING B. 167°F (75°C) MAX TEMP RATING C. 300V MAX VOLTAGE RATING								/IRING	W				MAX WIR INSUL D	
2. MATERIAL: A. STAMPING: .016" [0.4] THICK BRASS, TIN PLATED B. HOUSING: VINYL STAMPING STAMPING													→		
	3. SEE www.panduit.com FOR PACKAGE QUANTITIES													- HOUSING	
	4. DIMENSIONS IN BRACKETS ARE METRIC EQUIV								ENT						
								LISTED 19X5 E78522	IS		1 ; ;	L			
											TITLE			NEOTO (407 OFFICE)	
A											STRONGHOLD MALE DISCONNECTS (187 SERIES) VINYL INSULATED #22-14 AWG CUSTOMER DRAWING ITEM REVISION NAME				
											DATASET FILE NAME			PANDUIT	
											UNLESS	00123SSN_DC/00 S otherwise spe SL tolerances A	CIFIED.	MATERIAL:	-
											.x ± .1 [:	2.54] .xxx :	.005 [.127]	SEE NOTES	
00DA/12	00	2/18	JHNU	TMR	RGB	DRAWING RELEASED				00123SS		TH.	_	DRAWING NUMBER: 0012355N-DC	
010100	REV	DATE	BY	СНК	APR		DESCRI	PTION		ECN	JHNU DATE	- RLS	N.T.S.	I I	A
- •	2									1					