



角型 品番	D1 先端径	D2 元端径	L 全長	H 角対辺	使用 ハンドル	使用ドリル 下穴寸法(mm)	使用寸法		本体質量 (g)	梱包重量 (g)	外箱梱包サイズ (D×W×H)	材質	入数
							ボルト(mm)	パイプ					
EX-801K	1.8	4.5	50	3.3	TH-6	2.5	4.8 ~ 6.4		5	180	112×78×40	S45C	36
EX-802K	2.0	5.6	60	4	TH-6	3.3	6.4 ~ 8		10	360	112×78×40	S45C	36
EX-803K	3.0	7.3	68	5.2	TH-6	4.5	8 ~ 11		15	540	155×90×50	S45C	36
EX-804K	5.0	8.7	76	6.3	TH-10	6.5	11 ~ 14		30	1080	155×90×50	S45C	36
EX-805AK	7.0	11	86	8	TH-13	8.0	14 ~ 19	1/8	40	1440	155×90×50	S45C	36
EX-805BK	8.7	13.5	86	9.3	TH-13	9.2	17 ~ 24	1/4	60	180	58×113×23	S45C	3
EX-806AK	9.5	15	95	11	TH-19	10.5	19 ~ 25		100	300	58×113×23	S45C	3
EX-806BK	12.0	17.5	95	14	TH-25	12.5	24 ~ 28	3/8	130	390	75×125×27	S45C	3
EX-807AK	12.7	20	105	15	TH-25	13.5	25 ~ 35		170	510	75×125×27	S45C	3
EX-807BK	15	22	105	17	TH-32	15.5	28 ~ 38	1/2	230	690	75×125×27	S45C	3
EX-808K	19	26	110	19	TH-32	20.5	35 ~ 44	3/4	340	360	125×45×32	S45C	1
EX-809K	25	33	120	24	TH-38	27	44 ~ 54	1"	570	360	125×45×32	S45C	1
EX-810K	32	40	127	30	TH-50	33.5	54 ~ 64	1 1/4	950	980	140×55×45	S45C	1
EX-811K	38	48	140	30	TH-50	40.0	64 ~ 76	1 1/2	1590	1630	165×60×55	S45C	1
EX-812K	48	58	160	30	TH-50	49.5	76 ~ 90	2"	2200	2240	165×60×55	S45C	1
(備考) 805A(AK)≒805 805B(BK)≒8051/4 806A(AK)≒806 806B(BK)≒8063/8 807A(AK)≒807 807B(BK)≒8071/2													