



Item No: TBRI

Item No.	Size	B		L1 ±2.0	L2 ±2.0	硬度 HRC	標準 トルク値	ボールポイント トルク値	レーザー内容	刻印内容
		max	min				N-M	(min)		
TBRI-0.05	0.05"	1.270	1.245	72.0	12.0	52~58°	0.6	0.3	TRUSCO TBRI-0.05 0.05"	
TBRI-1/16	1/16	1.587	1.563	77.0	14.0		1.2	0.7	TRUSCO TBRI-1/16 1/16"	
TBRI-5/64	5/64	1.983	1.959	82.0	15.0		2.4	1.3	TRUSCO TBRI-5/64 5/64"	
TBRI-3/32	3/32	2.379	2.355	88.0	17.0		4.2	2.3	TRUSCO TBRI-3/32 3/32"	
TBRI-7/64	7/64	2.778	2.741	92.0	18.0		6.7	3.7	TRUSCO TBRI-7/64 7/64"	
TBRI-1/8	1/8	3.175	3.137	96.0	19.0		9.7	5.3	TRUSCO TBRI-1/8	CR-V 1/8
TBRI-9/64	9/64	3.571	3.534	101.0	20.0		14.1	7.8	TRUSCO TBRI-9/64	CR-V 9/64
TBRI-5/32	5/32	3.967	3.930	105.0	21.0		19.2	10.6	TRUSCO TBRI-5/32	CR-V 5/32
TBRI-3/16	3/16	4.762	4.725	114.0	24.0		33.3	18.3	TRUSCO TBRI-3/16	CR-V 3/16
TBRI-7/32	7/32	5.554	5.517	124.0	26.0		48.0	26.4	TRUSCO TBRI-7/32	CR-V 7/32
TBRI-1/4	1/4	6.350	6.312	135.0	28.0	50~58°	71.2	39.2	TRUSCO TBRI-1/4	CR-V 1/4
TBRI-5/16	5/16	7.937	7.902	151.0	32.0		141.0	77.6	TRUSCO TBRI-5/16	CR-V 5/16
TBRI-3/8	3/8	9.525	9.487	170.0	35.0		243.0	133.7	TRUSCO TBRI-3/8	CR-V 3/8

単位 : mm