



品番	B2 ±0.8	A2 ±0.8	B1 ±0.8	A1 ±0.8	B3 ±0.8	A3 ±0.8	L ±2.5	C
TMS-055	14.6	3.4	9.6	4.0	6.0	2.1	93	5.52-5.62
TMS-06	16.5	3.7	10.5	4.5	7.0	2.3	100	6.03-6.15
TMS-07	18.3	3.7	11.6	5.0	7.5	2.4	110	7.03-7.15
TMS-08	20.5	4.1	13.4	5.5	8.8	2.8	120	8.03-8.15
TMS-09	22.4	4.1	14.8	6.0	9.4	3.0	130	9.03-9.15
TMS-10	24.0	4.6	16.1	6.5	9.8	3.2	140	10.04-10.19
TMS-11	26.0	4.7	17.7	6.5	10.6	3.5	150	11.04-11.19
TMS-12	27.8	4.8	19.1	7.0	11.4	3.6	160	12.04-12.24
TMS-13	28.8	5.5	20.5	7.5	12.0	3.9	170	13.04-13.24
TMS-14	31.8	5.6	22.2	8.0	12.6	4.2	180	14.05-14.27
TMS-15	34.5	5.7	23.6	8.5	13.5	4.3	190	15.05-15.27
TMS-16	36.6	5.8	24.8	9.0	14.0	4.3	200	16.05-16.27
TMS-17	38.6	6.3	26.4	9.5	15.0	4.5	210	17.05-17.30
TMS-18	39.4	6.8	27.7	10.0	15.4	4.6	220	18.05-18.30

品番	B2 ±0.8	A2 ±0.8	B1 ±0.8	A1 ±0.8	B3 ±0.8	A3 ±0.8	L ±2.5	C
TMS-19	42.5	7.1	29.2	10.4	15.9	4.7	230	19.06-19.36
TMS-21	45.2	7.5	31.8	11.4	17.4	5.1	250	21.06-21.36
TMS-22	48.6	8.0	33.4	11.9	18.5	5.4	260	22.06-22.36
TMS-24	51.0	8.2	35.8	12.9	19.5	5.6	280	24.06-24.36
TMS-26	52.7	8.7	38.4	13.4	21.0	6.0	295	26.08-26.48
TMS-27	56.0	8.9	40.3	14.4	22.2	6.2	310	27.08-27.48
TMS-30	60.5	10.0	44.7	15.9	24.2	6.5	340	30.08-30.48
TMS-32	65.0	10.8	47.5	16.9	25.2	6.9	360	32.08-32.48

硬度 : HRC 38-55

単位 : mm