



Item No

Item No.	対辺寸法	B		L1 ±2.0	L2 ±2.0	硬度 HRC	トルク N-M (min)	レーザー内容	刻印内容
		max	min						
TRRL-15	1.5	1.50	1.48	90.0	14.0	52~58°	1.0	<b>TRUSCO</b> 1.5mm	/
TRRL-20	2.0	2.00	1.96	100.0	16.0		2.1	<b>TRUSCO</b> 2.0mm	
TRRL-25	2.5	2.50	2.46	112.0	18.0		4.7	<b>TRUSCO</b> TRRL-25 2.5mm	
TRRL-30	3.0	3.00	2.96	126.0	20.0		7.7	<b>TRUSCO</b> TRRL-30	CR-V 3mm
TRRL-40	4.0	4.00	3.95	140.0	25.0		17.8	<b>TRUSCO</b> TRRL-40	CR-V 4mm
TRRL-45	4.5	4.50	4.45	150.0	26.0		26.0	<b>TRUSCO</b> TRRL-45	CR-V 4.5mm
TRRL-50	5.0	5.00	4.95	160.0	28.0		35.0	<b>TRUSCO</b> TRRL-50	CR-V 5mm
TRRL-55	5.5	5.50	5.45	170.0	30.0		46.0	<b>TRUSCO</b> TRRL-55	CR-V 5.5mm
TRRL-60	6.0	6.00	5.95	180.0	32.0		57.0	<b>TRUSCO</b> TRRL-60	CR-V 6mm
TRRL-70	7.0	7.00	6.94	190.0	34.0		88.0	<b>TRUSCO</b> TRRL-70	CR-V 7mm
TRRL-80	8.0	8.00	7.94	200.0	36.0	50~58°	126.0	<b>TRUSCO</b> TRRL-80	CR-V 8mm
TRRL-100	10.0	10.00	9.94	224.0	40.0		252.0	<b>TRUSCO</b> TRRL-100	CR-V 10mm
TRRL-120	12.0	12.00	11.89	250.0	45.0	48~53°	420.0	<b>TRUSCO</b> TRRL-120	CR-V 12mm
TRRL-140	14.0	14.00	13.89	280.0	56.0		670.0	<b>TRUSCO</b> TRRL-140	CR-V 14mm
TRRL-170	17.0	17.00	16.89	320.0	63.0		1180	<b>TRUSCO</b> TRRL-170	CR-V 17mm
TRRL-190	19.0	19.00	18.87	360.0	70.0		1670	<b>TRUSCO</b> TRRL-190	CR-V 19mm

単位:mm

作成日 2012.02.14

検図

商品部

**TRUSCO** トラスコ中山株式会社

品名

六角棒レンチ  
(ロングタイプ)

品番

TRRL~