



Item No: TXX

Item No.	Size	B		L1 ±2.0	L2 ±2.0	硬度 HRC	トルク値 N-M (min)	レーザー内容	刻印内容
		max	min						
TXX-15	1.5	1.50	1.48	77.0	14.0	55~60°	1.0	TRUSCO TXX-15 1.5mm	
TXX-20	2.0	2.00	1.96	83.0	16.0		2.1	TRUSCO TXX-20 2.0mm	
TXX-25	2.5	2.50	2.46	90.0	18.0		4.7	TRUSCO TXX-25 2.5mm	
TXX-30	3.0	3.00	2.96	98.0	20.0		7.7	TRUSCO TXX-30	SNCMV 3mm
TXX-40	4.0	4.00	3.95	106.0	25.0		17.8	TRUSCO TXX-40	SNCMV 4mm
TXX-50	5.0	5.00	4.95	118.0	28.0		35.0	TRUSCO TXX-50	SNCMV 5mm
TXX-60	6.0	6.00	5.95	137.0	32.0		57.0	TRUSCO TXX-60	SNCMV 6mm
TXX-80	8.0	8.00	7.94	156.0	36.0		126.0	TRUSCO TXX-80	SNCMV 8mm
TXX-100	10.0	10.00	9.94	170.0	40.0	48~53°	252.0	TRUSCO TXX-100	SNCMV 10mm
TXX-120	12.0	12.00	11.89	207.0	45.0		420.0	TRUSCO TXX-120	CR-V 12mm
TXX-140	14.0	14.00	13.89	230.0	56.0		670.0	TRUSCO TXX-140	CR-V 14mm

単位 : mm