



単位：mm

一般鋼管用Uボルト ナット付 ステンレス			M6			M8			M10			M12			M16		
ねじ径			W	L	T	W	L	T	W	L	T	W	L	T	W	L	T
管呼称	適用管外径 (ϕ D)	(ピッチ)	(高さ)	(ねじ長)	(ピッチ)	(高さ)	(ねじ長)	(ピッチ)	(高さ)	(ねじ長)	(ピッチ)	(高さ)	(ねじ長)	(ピッチ)	(高さ)	(ねじ長)	
8A	1/4B	13.8	21	27	15												
10A	3/8B	17.3	25	33	18	27	38	24	28	43	28						
15A	1/2B	21.7	29.5	36	18	31	42	24	34	46	30						
20A	3/4B	27.2	34	42	18	37	48	24	40	51	30						
25A	1"B	34.0	41	49	25	44	54	25	46	59	30						
32A	1-1/4B	42.7	50.5	57	25	52	62	30	56	68	30	57	70	35			
40A	1-1/2B	48.6	57	68	25	59	67	30	62	74	30	63	81	35			
50A	2"B	60.5	70	80	30	72	80	30	74	85	30	76	90	35			
65A	2-1/2B	76.3				86	96	30	88	107	35	90	107	45			
80A	3"B	89.1				99	109	30	101	117	35	103	119	45			
90A	3-1/2B	101.6							115	132	35						
100A	4"B	114.3							126	145	35	129	150	45	134	151	60
125A	5"B	139.8							152	175	40	154	175	45	160	175	60
150A	6"B	165.2							180	200	40	182	200	45	186	202	60
200A	8"B	216.3							230	250	50	232	252	45	236	254	60
250A	10"B	267.4										282	307	50	286	308	60
300A	12"B	318.5													341	368	70
350A	14"B	355.6													376	401	70
400A	16"B	406.4													426	454	70
450A	18"B	457.2													478	508	75
500A	20"B	508.0													529	560	80

※一部寸法が異なる場合がございます。